Radio Frequency Drying Systems for the Paper Converting Industry Single Pass Web

SPW Series



Features

- · Increased line speed
- Moisture profiling
- No blocking
- No radiated heat
 - Meets CE and current emission regulations
 - · Selective drying of water based adhesive and coatings not substrate

SPW Series Standard Models (Non standard models also available to order)

SPW 6/37, SPW 6/55, SPW 12/37, SPW 12/55, SPW 12/73, SPW 12/109, SPW 25/55, SPW 25/73, SPW 25/209



- · Complete drying control
- Designed for continuous web finishing lines
- Remoist
- Pressure seal
- Designed to fit inline with web finishing equipment for maximum operational flexibility and efficiency
- Available with 6kW, 12kW or 25kW continuously rated radio frequency power sources, all operate on ISM Bands (Industrial, Scientific, Medical designated frequencies)

Strayfield Limited, Ely Road, Theale, Berkshire, England. RG7 4BQ Tel: +44 (0)870 428 1086 Fax: +44 (0)870 428 1087 E-mail: info@strayfield.co.uk Web: http://www.strayfield.co.uk/



Technical Specification

SPW Series Standard Models (Non standard models also available to order)

SPW 6/37, SPW 6/55, SPW 12/37, SPW 12/55, SPW 12/73 SPW 12/109, SPW 25/55, SPW 25/73 SPW 25/109

Model	SPW/37	SPW/55	SPW/73	SPW/109	Typical Production Speeds	
Drying length mm	1768	1588 1948	1588 1948	1588 1768 1948	120 mtrs/min 150 mtrs/min 165 mtrs/min 180 mtrs/min 214 mtrs/min	

Radio Frequency Generator 6kW, 12kW, 25kW							
Maximum Possible Water Removable Rate	6kW = 6 kgs/hr 12kW = 12 kgs/hr 25kW = 25 kgs/hr						
Power output (Continuously Rated)	6kW, 12kW, 25kW						
Frequency Standard Mains Supply	27.12 MHz ± 0.6% Stabilised (ISM Band) 360/440 Volt 3 Phase 50 Hz 440/510 Volt 3 Phase 60 Hz						
Maximum Line Current	6kW 12kW 25kW	400V@50Hz 17A 34A 70A	460V@60Hz 15A 30A 60A				
Maximum Power Consumption	6kW 12kW 25kW	12kVA 24kVA 48kVA	-				
Oscillator Valve	6kW 12kW 25kW	BR 1196 ITL 12 ITL 12	- RS 3010				
Rectifiers	Silicon Dio	con Diodes					

Strayfield has a policy of continued improvement and reserves the right to alter specification at any time without notice.

For details of guarantee refer to Strayfield Terms and Conditions of Sale.

